



# XTC COMPOSITE 29ER 1

THE QUICK, SHARP FEEL OF A LIGHTWEIGHT COMPOSITE HARTAIL. THE CONTROL OF 29-INCH WHEELS. XC RACERS CAN HAVE IT ALL.



## SPECIFICATIONS

FRAME	
SIZES	S, M, L, XL
COLORS	Satin Composite/Silver/Green
FRAME	Giant Composite Technology
FORK	Fox Float F29 Evolution CTD w/ 15QR thru-axle, OverDrive 2, 100mm Travel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect, Riser, 31.8
STEM	Giant Connect SL, OverDrive 2
SEATPOST	Giant Connect SL, 30.9
SADDLE	Fi'zi:k Tundra 2 w/ Manganese Rails
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX, 2x10 Speed
FRONT DERAILLEUR	Shimano SLX
REAR DERAILLEUR	Shimano Deore XT
BRAKES	Shimano SLX, 160mm
BRAKE LEVERS	Shimano SLX
CASSETTE	Shimano HG62 11x36, 10-Speed
CHAIN	KMC X10
CRANKSET	Shimano Deore XT, 26/38
BOTTOM BRACKET	Shimano, Press Fit
WHEELS	
RIMS	Giant P-XC29er 2, Double Wall
HUBS	[F] Giant Tracker Sealed/CNC w/ 15mm Axle, [R] Giant Tracker Performance, 32h
SPOKES	DT Swiss Competition, 14/15g
TIRES	Schwalbe Racing Ralph, 29x2.1 Performance Folding
OTHER	
EXTRAS	

## FRAME DESIGN

For XC racers and riders who want it all: the stability and control of a 29er, but with zero compromises in speed and quickness. Built with Giant Composite technology, and meticulously engineered to optimize the larger diameter wheels, this versatile hardtail uses Giant's signature oversized MegaDrive downtube and toptube combination for supreme chassis stiffness. The OverDrive 2 steerer tube produces quick, precise steering. And the asymmetrical chainstays paired with a PowerCore bottom bracket boost traction and acceleration.



## KEY UPGRADES (OVER XTC COMPOSITE 29ER 3):

- Fox Float Evolution CTD with QR15 thru-axle, OverDrive 2 steerer suspension fork
- Shimano Deore XT/SLX 2x10-speed shifting with Shimano SLX brakes
- Giant P-XC29er 2 double wall rims, Giant Tracker hubs, DT Swiss Competition butted spokes wheelset

## FRAME GEOMETRY

SIZE	PART NUMBER	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAINSTAY	WHEELBASE	STANDOVER HEIGHT***
Inches		Degrees	Degrees	Inches	Inches	Inches	Inches	Inches
S/16	30032614	71.0	73.0	22.6	4.1	17.3	41.8	28.5
M/18	30032615	71.5	72.5	23.4	4.1	17.3	42.1	29.6
L/20	30032616	71.5	72.0	24.2	4.3	17.3	42.7	30.5
XL/22	30032617	71.5	72.0	25.0	4.7	17.3	43.5	31.6

\*Seat angle is actual

\*\*Tuptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire